

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Claims 1-12 (canceled).

13. (New) A method for selectively providing a coupling between a first mechanical device and a second mechanical device, comprising:

providing an electromechanical coupling unit having at least two coupling windings, wherein the coupling unit is configured to provide selective coupling between the first and second mechanical devices, and wherein each of the coupling windings is configured to be supplied with electrical energy by at least one connected electrical control unit;

actuating the coupling unit to be closed if none of the two coupling windings are supplied with electrical energy, whereby the coupling unit provides a coupling between the first and second mechanical devices; and

actuating the coupling unit to be open if at least one of the two coupling windings is supplied with electrical energy, whereby the coupling unit provides no coupling between the first and second mechanical devices.

14. (New) The method as recited in Claim 13, wherein at least one electrical control unit is respectively assigned to each of the first and second mechanical devices, wherein each electrical control unit selectively supplies, using at least one trigger element, the respective connected coupling

winding with electrical energy, as a function of state of the respective connected coupling winding.

15. (New) The method as recited in Claim 14, wherein each connected electrical control unit has a respective assigned power supply.

16. (New) The method as recited in Claim 14, wherein the electrical control units connected to the coupling windings are each assigned to one of the two mechanical devices.

17. (New) The method as recited in Claim 13, wherein at least one electrical control unit is assigned to the first mechanical device and at least one further electrical control unit is assigned to the second mechanical device.

18. (New) The method as recited in Claim 14, wherein the electrical control units detect, with the aid of sensors, the functioning of the coupling unit.

19. (New) The method as recited in Claim 14, further comprising:

implementing a functional test of the coupling windings, wherein each individual coupling winding is cut off from supply of electrical energy for a brief predetermined period and the coupling unit remains open during the functional test.

20. (New) A steering system for selectively providing a coupling between a first mechanical device and a second mechanical device, comprising:

Express Mail No.: EV 839709265 US

NY01 1147360 v1

an electromechanical coupling unit having at least two coupling windings, wherein the coupling unit is configured to provide selective coupling between the first and second mechanical devices; and

a plurality of electrical control units, wherein each coupling winding is connected to at least one of the electrical control units, and wherein each of the coupling windings is configured to be supplied with electrical energy by at least one connected electrical control unit;

wherein the coupling unit is configured such that the coupling unit is: a) closed if none of the two coupling windings are supplied with electrical energy, whereby the coupling unit provides a coupling between the first and second mechanical devices; and b) open if at least one of the two coupling windings is supplied with electrical energy, whereby the coupling unit provides no coupling between the first and second mechanical devices.

21. (New) The steering system as recited in Claim 20, wherein the first mechanical device is a steering handle and the second mechanical device is a steered vehicle wheel.

22. (New) The steering system as recited in Claim 21, further comprising:

at least one sensor for detecting the functioning of the coupling unit.

23. (New) The steering system as recited in Claim 21, wherein at least one electrical control unit includes at least one trigger element for supplying the connected coupling winding with electrical energy.

24. (New) The steering system as recited in Claim 21, further comprising:

at least one data line for exchanging information between the electrical control units.